

SAFETY DATA SHEET

Issue Date 13-Dec-2012 Revision Date 26-Mar-2013 Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Industrial Grade Silicone – Acetoxy Cure – Clear, White & Colors

Other Means of Identification

SDS # RD-0080A

Product Code 0816/OI, 0826OI Series

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Silicone Sealant.

Details of the Supplier of the Safety Data Sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

Emergency Telephone Number

Company Phone Number 918-825-5744 Fax: 918-825-5761

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation Category 2

Signal Word Warning

Hazard Statements Causes skin irritation



Appearance Clear/opaque or colored paste

Physical State Paste

Odor Acetic Acid Odor (Vinegar odor)

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water If skin irritation persist: Get medical advice/attention Take off contaminated clothing and wash before reuse

Hazards Not Otherwise Classified (HNOC)

Not Applicable

Other Information

Not Applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hydroxy-terminated Dimethyl siloxane	70131-67-8	>50
Non-hazardous ingredients *	Proprietary	>10
Amorphous silica (glass)	7631-86-9	<13
Polydimethylsiloxane	63148-62-9	<10
Methyltriacetoxysilane	4253-34-3	<6
Titanium Dioxide	13463-67-7	<5
Ethyltriacetoxysilane	17689-77-9	<6

^{*} Unlisted ingredients are not considered hazardous under the OSHA GHS Hazard Communication Standard (29 CFR 1910.1200). (Methyltriacetoxysilane) Observe limits for acetic acid formed during curing on exposure to water or humid air. (Silica, amorphous; Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state

4. FIRST AID MEASURES

First Aid Measures

General advice Provide this SDS to medical personnel for treatment.

Inhalation If symptoms are experienced remove source of contamination or move victim to fresh air. If

irritation persists, obtain medical advice.

Eye Contact Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5

minutes while holding the eyelid(s) open. Obtain medical attention.

Ingestion Rinse mouth thoroughly with water. If irritation or discomfort occurs, obtain medical advice.

Skin Contact No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water

for 5 minutes. If irritation persists, obtain medical advise.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Causes skin irritation. May cause nose, throat & respiratory tract irritation. Direct contact

with eyes may cause temporary irritation.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians

Treat according to person's condition & specifics of exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire

Use carbon dioxide (CO2), dry chemical or water spray.

Large Fire

Use dry chemical, foam or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion products Carbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

Protective Equipment and Precautions for Firefighters

Self-contained breathing apparatus & protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Observe all personal protection equipment recommendations described in Sections 5 & 8.

Environmental Precautions

See Section 12 for additional ecological information.

Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up

Wipe up or scrape up & contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state & federal laws & regulations may apply to releases & disposal of this material as well as those materials & items employed in the cleanup of releases. You will need to determine which federal, state & local laws & regulations are applicable. Sections 13 & 15 of this MSDS provide information regarding certain federal & state requirements.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands, and any exposed skin thoroughly after handling. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Avoid contact with skin and eyes. Product evolves acetic acid (HOAc) when exposed to water or humid air.

& Colors

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep container closed & store away from water or moisture.

Incompatible Materials Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous

vapors to form as described in Section 8.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Amorphous silica (glass) 7631-86-9	-	(vacated) TWA: 6 mg/m³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO2) mg/m³ TWA	IDLH: 3000 mg/m³ TWA: 6 mg/m³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m ³

Acetic acid is formed upon contact w/ water or humid air. Provide adequate ventilation to Other Information

control exposures within quidelines of OSHA PEL: TWA 10 ppm & ACGIH TLV: TWA 10

ppm, STEL 15 ppm.

Appropriate Engineering Controls

Ventilation must be adequate to maintain the ambient workplace atmosphere below the **Engineering Controls**

exposure limit(s) outlined in the SDS. Good general ventilation should be sufficient.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Safety glasses as a minimum for protection.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection No special equipment needed.

Note: These precautions are for room temperature handling. Use @ elevated temperature **General Hygiene Considerations**

or aerosol/spray applications may require added precautions. Handle in accordance with good industrial hygiene and safety practice. Wash @ mealtime & end of shift. Contaminated clothing & shoes should be removed as soon as practical & thoroughly cleaned before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Paste

Odor Acetic Acid Odor (Vinegar Clear/opaque or colored paste **Appearance**

odor)

Not determined Odor threshold Color Various

Remarks • Method **Property** Values

Not determined Not determined Melting point/freezing point Not determined Boiling point/boiling range Not applicable Flash point

& Colors

Evaporation rate Flammability (solid, gas)

Not determined Not determined

Flammability limits in air

Upper flammability limits Not determined Lower flammability limit Not determined Not determined Vapor pressure Vapor density Not determined ~1 04

@ 25 °C (77 °F)

Specific gravity Water solubility

Not determined Solubility in other solvents Not determined . Partition coefficient Not determined Not determined Autoignition temperature **Decomposition temperature** Not determined Kinematic viscosity Not determined Not determined **Dynamic viscosity** Not determined **Explosive properties**

Other Information

Oxidizing Properties

Additional information VOC Content (%)

Note: The above information is not intended for use in preparing product specifications

< 3%/wt (< 40 g/L)

Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials.

Incompatible Materials

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde, Nitrogen oxides & metal oxides.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

May cause irritation of respiratory tract. Inhalation

May cause temporary irritation on eye contact. **Eye Contact**

Skin Contact Causes skin irritation. Can be absorbed through the skin. Ingestion

Can be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50		
Amorphous silica (glass) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h		
Polydimethylsiloxane 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	-		
Methyltriacetoxysilane 4253-34-3	= 2060 mg/kg (Rat)	-	-		
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	•	•		

Information on Physical, Chemical and Toxicological Effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous silica (glass) 7631-86-9		Group 3	-	
Titanium Dioxide 13463-67-7		Group 2B		Х

IARC (International Agency for Research on Cancer)

Group 28 - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical Measures of Toxicity- Product

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Amorphous silica (glass)	-	5000: 96 h Brachydanio rerio		7600: 48 h Ceriodaphnia
7631-86-9	Pseudokirchneriella subcapitata mg/L EC50	mg/L LC50 static		dubia mg/L EC50

Persistence and Degradability

Complete information is not yet available.

Bioaccumulation

Complete information is not yet available.

Mobility

Complete information is not yet available.

& Colors

Other Adverse Effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal should be in accordance with applicable regional, national and local laws and **Disposal of Wastes**

regulations.

Disposal should be in accordance with applicable regional, national and local laws and **Contaminated Packaging**

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances

DOT Not regulated

Not regulated IATA

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 311/312 Hazard Categories

Acute health hazard No **Chronic Health Hazard** No Fire hazard No Sudden release of pressure hazard No **Reactive Hazard** No

US State Regulations

Chemical Name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Amorphous silica (glass) 7631-86-9	Х	X	Х
Titanium Dioxide 13463-67-7	Х	X	Х

16. OTHER INFORMATION

U.S. EPA Label Information

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	4	•	0	D 0-1-1 01

1 0 0 B- Safety Glasses, Gloves

Issue Date 13-Dec-2012 Revision Date 26-Mar-2013

Revision Note New format Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet