

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

XTREME CLEAN CARGO

Product Number: 2047

Product Division: Janitorial

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990 Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Non-Hazardous Products

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate	Health: 2 - Moderate
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

		T T		Table Z-1-A		
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Tetrasodium EDTA	5-10	64-02-8	Not Established	Not Established	Not Established	No
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No
Phosphate ester	1-5	68130-47-2	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Not determined
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 11.5- 12.0	Specific Gravity (H,O=1): 1.06
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 10-15
Physical State: Liquid	
Appearance & Odor: Rose colored liquid, bland odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combus	stion. Use extinguishing media appropriate for surrounding fire.
containers with water spray.	ained breathing apparatus and protective clothing. Cool fire-exposed
Unusual Fire & Explosive Hazards: Combustion products are toxic.	

Threshold Limit Value:	Causes severe eye initation: Sympt	nme may include pain out	Intry: Inhalation, Skin Contact, Eyes; Oral
	Causes severe eye initiation: Symptoms me		
	May be harmful if swallowed: Symptom		
		e respiratory irritation: Syr	mptoms may include nasal discomfort and
	coughing.	alathina. Do not avalleu	v. Avoid breathing product mist. Wash
	thoroughly after handling .	cioning. Do not swanow	r. Avoid bieauting product mist. wasi
Conditions Aggravated by Use:		reexisting skin; eve and res	piratory disorders including asthma and
Guilliand (Igg. DV alod b) Goo.	dermatitis.	ourising sam, eye and res	prototy disorders including assima and
Emergency & First Aid Procedures:			
Eyes	Flush eyes with water for at least 15	minutes. Remove contact le	enses. Get medical attention.
Skin			at 15 minutes. Get medical attention if
	iπitation persists. Wash contaminate	ed clothing before reuse.	
Ingestion	Do not induce vomiting. Drink one o	r two glasses of water to dil	ute product. Get medical attention. Do
	not give anything by mouth to an und	_	
Inhalation:	In case of respiratory irritation or diza	ziness; move person to frest	n air. Get medical attention if irritation
	persists.	<u> </u>	
SECTION VI: REACTIVITY DATA			
Stability:	Stable	Incompatible Mate	rials: Strong oxidizing agents
	Signie		
	None	Hazardous Polymeriza	
SECTION VII: SPILL OR LEAK PROC	None EEDURES Small spills of one gallon or less may	Hazardous Polymeriza	ation: Will Not Occur
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled:	None CEDURES Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spil	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w	ation: Will Not Occur vater to sanitary sewer system (If iills with inent material and transfer liquid
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled:	None CEDURES Small spills of one gallon or less may permitted by local sewer regulations	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w	ation: Will Not Occur vater to sanitary sewer system (If iills with inent material and transfer liquid
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method:	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, ste	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w	ation: Will Not Occur vater to sanitary sewer system (If iills with inent material and transfer liquid
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION	None EDURES Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, states on INFORMATION	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations.	ation: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid aterways.
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good ge	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations.	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid aterways. However, if exposure limits (see Section
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION	None EDURES Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, states on INFORMATION	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NiOSH	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid aterways. However, if exposure limits (see Section approved respirator suitable for the
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: ECTION VIII: SPECIAL PROTECTION Respiratory Protection:	Small spills of one gallon or less may permitted by local sewer regulations; to containers for disposal. Keep spill Assure conformance with federal, standard Content of the content of th	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered	ation: Will Not Occur Pater to sanitary sewer system (If sills with inert material and transfer liquid aterways. However, if exposure limits (see Section approved respirator suitable for the
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection:	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, statement of the second series of the second serie	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH otion II should be considered cal exhaust ventilation may	ation: Will Not Occur Pater to sanitary sewer system (If ill with inert material and transfer liquid aterways. However, if exposure limits (see Section approved respirator suitable for the I. be necessary for some operations.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: ECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type):	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good ge II) are exceeded or respiratory irritationse-conditions and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. heral ventilation is provided on occurs, use of a NiOSH tion II should be considered cal exhaust ventilation may re recommended when han	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: ECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type):	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good ge II) are exceeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended we	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: ECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type):	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good ge II) are exceeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended we	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment:	Small spills of one gallon or less may permitted by local sewer regulations; to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good ge II) are exceeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended with the section of the secti	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment: SECTION IX: SPECIAL PRECAUTION	Small spills of one gallon or less may permitted by local sewer regulations; to containers for disposal. Keep spill Assure conformance with federal, state of the sexual series o	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment: SECTION IX: SPECIAL PRECAUTION Precautions; Handling & Storing:	Small spills of one gallon or less may permitted by local sewer regulations; to containers for disposal. Keep spill Assure conformance with federal, state on the sexual series of the sexual series o	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment: SECTION IX: SPECIAL PRECAUTION	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good gell) are exceeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended with Section 1910.132-138 for further the Section 1910.132-138 for further	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.
SECTION VII: SPILL OR LEAK PROCE Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment: SECTION IX: SPECIAL PRECAUTION Precautions; Handling & Storing:	Small spills of one gallon or less may permitted by local sewer regulations; to containers for disposal. Keep spill Assure conformance with federal, state on the sex seeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended with Section 1910.132-138 for further the sex sex sex sex sex sex sex sex sex se	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han then handling undiluted processors	rater to sanitary sewer system (If ills with inert material and transfer liquid aterways. However, if exposure limits (see Section approved respirator suitable for the limits and transfer liquid aterways.
SECTION VII: SPILL OR LEAK PROCE Steps to be Taken in Case Material is Released or Spilled: Waste Disposal Method: SECTION VIII: SPECIAL PROTECTION Respiratory Protection: Ventilation: Protective Gloves(Specify Type): Eye Protection(Specify Type): Other Protective Equipment: SECTION IX: SPECIAL PRECAUTION Precautions; Handling & Storing: Other Precautions:	Small spills of one gallon or less may permitted by local sewer regulations to containers for disposal. Keep spill Assure conformance with federal, state ON INFORMATION Not normally required when good gell) are exceeded or respiratory irritations and chemicals in Section Provide good general ventilation. Local Rubber or other impervious gloves a Splash goggles are recommended with See 29 CFR 1910.132-138 for further the section of the s	Hazardous Polymeriza be flushed with plenty of w Dike and contain large sp out of storm sewers and w ate and local regulations. meral ventilation is provided on occurs, use of a NIOSH tion II should be considered cal exhaust ventilation may re recommended when han hen handling undiluted proc r guidance.	ration: Will Not Occur rater to sanitary sewer system (If ills with inert material and transfer liquid atterways. However, if exposure limits (see Section approved respirator suitable for the l. be necessary for some operations. dling undiluted product.

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.